

**AHRI Rated Cooling Performance**

AHRI Certified Reference #	216013443
AHRI Rated Cooling Capacity	72,000 Btuh
EER	10.00
Rated Airflow	1900 cfm

**Supply Air Performance**

Total Supply Air	1903	cfm
Blower Motor	3/4	hp
Low Blower Speed		
Non-Ducted		

Air flow is based on Wet Coil

**Cooling Performance @ Project Parameters**

Cooling Capacity	72,019	Btuh
Sensible Capacity	50,133	Btuh
Latent Capacity	21,886	Btuh
Efficiency (at AHRI)	11.00	EER
Outdoor DB Temp	95.0	°F
Entering DB Temp	80.0	°F
Entering WB Temp	67.0	°F
Leaving DB Temp	55.6	°F
Leaving WB Temp	54.9	°F

**Electrical Data**

Power Supply	460	Volts
	3	Phase
	60	Hertz
Minimum Circuit Ampacity	17	Amps
Maximum External Fuse or Circuit Breaker	20	Amps

All wiring must conform to the National Electrical Code and all local codes

NOTE: MOCP (Maximum Overcurrent Protection) value listed is the maximum value as per UL 1995 calculations for MOCP (branch-circuit conductor sizes shown are based on this MOCP). The actual factory installed Overcurrent Protective Device (Circuit Breaker) in this model may be lower than the maximum UL 1995 allowable MOCP value, but still above the UL 1995 minimum calculated value or Minimum Circuit Ampacity (MCA) listed.

**Approximate Installed Weight**

Total Weight	565	lb
--------------	-----	----

**Factory Options Selected**

C - 460 Volt 3 phase  
00 - No Heat With Lug Connection  
X - Barometric Fresh Air Damper  
X - 1-inch Fiberglass MERV 2  
X - Beige  
X - Standard Cabinet, blow thru condenser fan  
X - Standard Coils  
X - Hi Pressure Switch, Low Pressure Switch, Compressor Control Module, & Refrigerant leak detector (RDS)



## Standard Product Features

### Wall-Mount Air Conditioner

- R-454B A2L Refrigerant that meets the global objectives outlined in the Montreal Protocol and the Kigali Amendment.
- Non-Fiberglass Foil Faced Insulation: Environmentally friendly high "R" value non-fiberglass insulation that is made with recycled denim and cotton materials used with a FSK foil face that is both durable and cleanable
- Durable Cabinet Construction: Multiple cabinet construction options are available for different outdoor conditions. Optional cabinet coatings may be ordered for extreme outdoor environments.
- Easy Filter Access: Dedicated filter door for simplified maintenance. Compatible with 1" and 2" filters up to MERV13 rating.
- Green Fin Hydrophilic Evaporator Coil: Enhanced wettability coating prevents mold formation, improves condensate drainage, and provides protection against corrosive airborne particulates.
- Copper/Aluminum Condenser Coil: Rifled copper tubing for increased efficiency and aluminum fins for easy cleaning and servicability.
- Multi-speed Electronically commutated indoor motor (ECM) technology.
- Enclosed outdoor fan motor with ball bearing construction.
- Copper/Aluminum finned coils, and refrigerant system includes filter drier. Evaporator coil includes green fin coil protection.
- Controls include short cycle protection and phase monitoring. Hi and low pressure switch refrigerant system protection standard.

### Series Compliance

- Complies with efficiency requirements of ANSI/ASHRAE/IESNA 90.1-2019.
- Certified to ANSI/AHRI Standard 390-2021 for SPVU (Single Package Vertical Units)
- Intertek ETL Listed to Standard for Safety of Household and Similar Electrical Appliances ANSI/UL STD 60335-1 & ANSI/UL STD 60335-2-40/ CSA STD C22.2 No. 60335-1 & CSA STD C22.2 No. 60335-2-40 Fourth Edition.
- Bard is an ISO 9001:2015 Certified Manufacturer

**Dimensions of Basic Unit for Architectural and Installation Requirements (Inches)**

Width (W)	Depth (D)	Height (H)	Supply		Return		E	F	G	I
			A	B	C	B				
42	25.52	93	9.88	29.88	15.88	29.88	43.88	12.63	45	30
J	K	L	M	N	O	R	S	T	U	V
59.75	35.06	61.72	58.72	8.82	43	1.438	16	10	13.88	15.43

